

Vacuum Ironing Tables

FIT2A, FIT2B



Features and benefits

- Heated to keep the working surface dry
- Utility shape for general purpose
- Integral vacuum fan holds the garment in place and dries the fabric after pressing
- Steam electric iron c/w separator versatile
- Integral boiler for simple installation

FIT2A

FIT2B

Main options

- Steam electric iron c/w separator
- Free standing boiler for simple installation
- Cold spotting gun(s) for removal of spots
- Steam gun for removal of spots
- Steam/air gun for removal of spots
- Sleeve arm for pressing awkward shapes
- Spotting arm for spotting
- Overhead gantry to support iron hoses
- Iron balancer reduces operator fatigue
- Light, illuminates the working area

X

X

X

X

X

X

-

X

-

X

X

-

X

-

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

x available
 - not available

| Electrical connections | | FIT2A | FIT2B |
|---|------------|---------|---------|
| Voltage | | | |
| 208-240V 1 AC 50/60 Hz | kW | 0.85 | - |
| 208-240V 3 AC 50/60 Hz | kW | - | 5.6 |
| 380-415V 3/3N AC 50/60 Hz | kW | - | 5.6 |
| Steam, air and vacuum connection | | | |
| Steam | DN | 10 | - |
| Rec. steam pressure | kPa | 400-600 | 200-250 |
| Steam consumption | kg/h | 4 | - |
| Condensate | DN | 15 | - |
| Water supply | mm | - | Ø12 |
| Boiler drain | DN | - | 10 |
| Compressed air | DN | 8 | - |
| Rec. air pressure | kPa | 500-700 | 600-700 |
| Air consumption | l/min | 300 | 300 |
| Vacuum outlet | mm | Ø100 | Ø100 |
| Shipping data | | | |
| | net, kg | 70 | 105 |
| | crated, kg | 100 | 135 |
| | boxed, kg | 140 | 175 |
| Dimensions in mm | | | |
| A Width | | 1520 | 1600 |
| B Depth | | 435 | 470 |
| C Height | | 920 | 920 |
| <ol style="list-style-type: none"> 1 Control panel 2 Electrical connection 3 Steam connection 4 Condensate 5 Air connection 6 Boiler drain 7 Water supply 8 Vacuum outlet | | | |



Model FIT2B shown

