



Professional Dryer

PD9C

Features and benefits

- PD9C is a large capacity tumble dryer for professional users
- With Compass Pro program control
 - A control knob for simple program selection and start
 - Large and clear display
 - Time and temperature selection for flexible use
- Anti-crease cycle for avoiding creasing if the dryer is not unloaded
- Low energy consumption for optimal efficiency
- Reversible door hanging for a convenient laundry flow
- Large door opening for easy loading/unloading
- White painted cabinet
- The coin version with Ecopower to avoid over drying of the garments and get a lower energy consumption

Options

- Payment: coinmeter with Ecopower
- Fresh air intake



Images shown are a representation of the product only and variations may occur.

Main specifications		PD9C	
Capacity, max	kg/lb	10.6/23.4	
Heating, electric	kW	6/8	
Consumption data*		6kW	8kW
Total time full load	min	47	37
Energy consumption full load	kWh	4.6	4.6
Evaporation	g/min	106	135
Energy kWh/litre water evaporated	kWh	0.92	0.92

* At rated capacity 100% cotton load at 50% initial moisture dried to 0%.

Certified in accordance with ISO 9001 and ISO 14001 and approved IP X4.



Electrical connections			PD9C
Heating Voltage			
El.	230-240V 1AC 50/60 Hz	kW(A)	6.3 (35)
	230V 3AC 50/60 Hz	kW(A)	8.3 (25)
	208-240V 3AC 60 Hz	kW(A)	6.3 (20)
	400V 3NAC 50/60 Hz	kW(A)	6.3 (10)
	400V 3NAC 50/60 Hz	kW(A)	8.3 (16)
Air connections			
Air outlet		ø mm	125
Evacuated air	6 kW (el)	m ³ /h	270
	8 kW (el)		290
Pressure drop	6 kW	Max. Pa	120
	8 kW		70
Sound levels			
Airborne sound level			
L _w		dB(A)	68
Heat emission			
% of installed power, max			15
Shipping data			
Shipping volume		net, kg	99
		crated, kg	114
		crated, m ³	0.8
Dimensions in mm			
A	Width		720
B	Depth		1408
C	Height		1114
D			79
E			935
F			724
<ol style="list-style-type: none"> 1 Operating panel 2 Door opening ø 400 mm 3 Electrical connection 4 Exhaust connection 			

* Other voltages available see installation manual.

